

Component - Plastics

E41797

Guide Information

TORAY INDUSTRIES INC

NIHONBASHI-MITSUI TOWER, 1-1 NIHONBASHI-MUROMACHI 2-CHOME, CHUO-KU TOKYO 103-8666 JP

100

Acrylonitrile Butadiene Styrene (ABS) "Toyolac", furnished as pellets

Color	Min. Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	1.5	HB	4	0	60	60	60
	3.0	HB	3	0	60	60	60
	6.0	HB	3	0	60	60	60

Comparative Tracking Index (CTI): 1
 Dielectric Strength (kV/mm): 35
 High-Voltage Arc Tracking Rate (HVTR): 1
 Dimensional Stability (%): 0

Inclined Plane Tracking (IPT) kV: -
 Volume Resistivity (10⁸ ohm-cm): 15
 High Volt, Low Current Arc Resis (D495): 5

NOTE - Polyamide (nylon) grades may be prefixed with the letters CM and may employ hyphens in various locations. The designations of ECODEAR products may employ hyphens and/or spaces in various locations. All grades that include ABS, SAN, and/or PC (designations of TOYOLAC or TOYOLAC PAREL or TORAYCA products) may employ hyphens and/or spaces and may be suffixed with 3 or 4 digits of letters and/or numbers.

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 1991-06-19
 Last Revised: 2017-11-06

© 2018 UL LLC



IEC and ISO Test Methods				
Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10	Class (color)	1.5	HB75 (ALL)
			3.0	HB40 (ALL)
			6.0	HB40 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	°C	-	-
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	°C	-	-
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	-
IEC Ball Pressure	IEC 60695-10-2	°C	-	-
ISO Heat Deflection (1.80 MPa)	ISO 75-2	°C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m ²	-	-
ISO Izod Impact	ISO 180	kJ/m ²	-	-
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	-