

UL认证

| | | |
|---------------|-------|---------|
| INFINO | Grade | NE-1030 |
|---------------|-------|---------|

iq.ul.com

Component - Plastics [\[guide info\]](#) E115797

Lotte Advanced Materials Co Ltd
56 Gosan-ro, Uiwang-si Gyeonggi-do 437-711 KR

NE-1030(+)
Polycarbonate/Acrylonitrile Butadiene Styrene (PC/ABS), "INFINO", furnished as pellets

| Color | Min Thk (mm) | Flame Class | HAI | | RTI | | RTI Str |
|-------|--------------|-------------|-----|-----|------|-----|---------|
| | | | HWI | HAI | Elec | Imp | |
| ALL | 1.0 | V-2 | - | - | 60 | 60 | 60 |
| | 1.5 | V-0 | - | - | 60 | 60 | 60 |
| | 2.0 | V-0 | - | - | 60 | 60 | 60 |
| | 3.0 | V-0 | - | - | 60 | 60 | 60 |

Comparative Tracking Index (CTI): - Inclined Plane Tracking (IPT): -
Dielectric Strength (kV/mm): - Volume Resistivity (10⁸ ohm-cm): -
High-Voltage Arc Tracking Rate (HVTR): - High Volt, Low Current Arc Resis (D495): -
Dimensional Stability (%): -

(+) - May be replaced by one, two, or three numbers and/or letter(s)

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2011-05-04
Last Revised: 2013-06-18 © 2016 UL LLC 

IEC and ISO Test Methods

| Test Name | Test Method | Units | Thk (mm) | Value |
|--------------------------------|-----------------|-------------------|----------|-----------|
| Flammability | IEC 60695-11-10 | Class (color) | 1.0 | V-2 (ALL) |
| | | | 1.5 | V-0 (ALL) |
| | | | 2.0 | V-0 (ALL) |
| | | | 3.0 | V-0 (ALL) |
| Glow-Wire Flammability (GWFI) | IEC 60695-2-12 | C | - | - |
| Glow-Wire Ignition (GWIT) | IEC 60695-2-13 | C | - | - |
| IEC Comparative Tracking Index | IEC 60112 | Volts (Max) | - | - |
| IEC Ball Pressure | IEC 60695-10-2 | C | - | - |
| ISO Heat Deflection (1.80 MPa) | ISO 75-2 | C | - | - |
| ISO Tensile Strength | ISO 527-2 | MPa | - | - |
| ISO Flexural Strength | ISO 178 | MPa | - | - |
| ISO Tensile Impact | ISO 8256 | kJ/m ² | - | - |
| ISO Izod Impact | ISO 180 | kJ/m ² | - | - |
| ISO Charpy Impact | ISO 179-2 | kJ/m ² | - | - |