 LG Chem LG Twin Tower/ East Wing, 20, Yoido-dong, Youngdungpo-gu Seoul 150-721, Korea Tel : 82-2-3773-7743 Fax : 82-2-3773-7660	M S D S		Reg. No.	YGN5001RFT
	(Material Safety Data Sheet)		Issue Date	2008. 9. 01
	PC Compound		Version	1.0
	LUPOY GN5001RFT		Revision Date	2008. 9. 01
			Page	1 / 5

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

- ① Product Name : LUPOY GN5001RFT
 ② Product Type : PC Compound
 ③ Ext. Appearance : Pellet type plastic solid
 ④ Purpose / Use : May be used to produce molded or extruded particles or as a component of other industrial products.
 ⑤ Manufacture : LG Chemical Ltd. Iksan Plant
 599, Yongjei-dong, Iksan-city, Chunbuk-do, 570-350, Korea
 Tel) 082-0653-830-4121, Fax) 082-0653-830-4036
 ⑥ Supplier : LG Chemical Ltd. / 20, Yoido-dong, Yongdungpo-gu, Seoul, 150-721, Korea
 Tel) 082-02-3773-1114, Fax) 082-02-3773-7766, 7111

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Common Name</u>	<u>CAS Number</u>	<u>Contents (%)</u>
Polycarbonate	PC	103598-77-2	65 ~ 75
BPADP	BPADP (Flame retardant)	181028-79-5	13 ~ 20
Acrylonitrile-Butadiene-Styrene Terpolymer	ABS	9003-56-9	5 ~ 15

3. HAZARDS IDENTIFICATION

NFPA RATINGS (SCALE 0-4) : HEALTH=1 FIRE=1 REACTIVITY=0

EC CLASSIFICATION (CALCULATED) : No classification assigned.

EMERGENCY OVERVIEWS :

Solid pellets with slight or no odor. Spilled pellets create slipping hazard.

Can burn in a fire creating dense toxic smoke. Molten plastic can cause severe thermal burns.

Fumes produced during melt processing may cause eye, skin and respiratory tract irritation.

Secondary operations, such as grinding, sanding or sawing, can produce dust which may present an explosion or respiratory hazard.

POTENTIAL HEALTH EFFECTS :

EYE : Product may cause irritation or injury due to mechanical action.

SKIN : Pellets not likely to cause skin irritation.

INGESTION : Not acutely toxic.


INHALATION : Pellet inhalation unlikely due to physical form.

CHRONIC / CARCINOGENICITY :

NTP : Not Tested

OSHA : Not Regulated

IARC : Not Listed

 LG Chem	PC Compound LUPOY GN5001RFT	Reg. No.	YGN5001RFT
		Version	1.0
		Page	2 / 5

4. FIRST AID MEASURES

MEDICAL RESTRICTIONS :

EYE : Remove contact lenses at once. Immediately flush eyes well with copious quantities of water or normal saline for at least 15–20 minutes. If irritation persists, seek medical attention.

SKIN : seek medical attention if rash or burn occurs.

INGESTION : Not probable. If a large amount is swallowed, seek medical attention.

INHALATION : Not Likely to be inhaled due to physical form.

MELT PROCESSING :

For molten plastic skin contact, cool rapidly flush water and immediately seek medical attention.

Do not attempt removal of plastic without medical assistance. Do not use solvent for removal.

For processing fume inhalation irritation, leave contaminated area and breathe fresh air. If coughing, difficult breathing or any other symptoms develop seek medical attention at once, even if symptoms develop at a later time.

For skin contact with fume condensate, immediately wash thoroughly with soap and water. If irritation develops seek medical attention.

5. FIRE FIGHTING MEASURES

FIRE FIGHTING :

Approved pressure demand breathing apparatus and protective clothing should be used for all fires. Water spray is the preferred extinguishing medium. This product will melt but will not be carried on the surface for water.

EXTINGUISHING MEDIA :

Water spray and foam, Water is the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition.

HAZARDOUS COMBUSTION PRODUCTS :

Hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide, oxides of phosphorus, hydrogen cyanide, hydrocarbon fragments, hydrogen fluoride, carbonyl fluoride and fluorocarbon fragments.

FLASH POINT : Not Applicable

LOWER FLAMMABLE LIMIT : Not Established

UPPER FLAMMABLE LIMIT : Not Established

AUTOIGNITION : Not Established


FLAMMABILITY CONDITIONS : Requires a continuous flame source to ignite and sustain combustion.

EXPLOSION DATA : Not Established

IMPACT SENSITIVITY : Not sensitive to mechanical impact.

STATIC DISCHARGE : Not sensitive to static discharge. (See Section 7)



 LG Chem	PC Compound LUPOY GN5001RFT	Reg. No.	YGN5001RFT
		Version	1.0
		Page	3 / 5

6. ACCIDENTAL RELEASE MEASURES

GENERAL :

Sweep or gather up material and place in proper container for disposal or recovery. (See Section 13)

7. HANDLING AND STORAGE

HANDLING :

Follow recommendations on label and in processing guide. Prevent contact with skin and eyes. Use good industrial hygiene practices. Provide adequate ventilation. Secondary operations such as grinding, sanding or sawing may produce a dust explosion hazard. Use aggressive housekeeping activities to prevent dust accumulation; employ bonding, grounding, venting and explosion relief provisions in accordance with accepted engineering practices.

STORAGE :

Store in a dry place away from moisture, excessive heat and sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS :

A continuous supply of fresh air to the workplace together with removal of processing fumes through exhaust systems is recommended. Processing fume condensate may be a fire hazard and toxic; remove periodically from exhaust hoods, duct work and other surfaces using appropriate personal protection. For powders and residual dusts refer to Section 7.


PERSONAL PROTECTION :

- EYE/FACE** : Wear safety glasses with side shields or chemical goggles. In addition, use full face shield when cleaning processing fume condensates from hoods, ducts and other surfaces.
- RESPIRATORY** : When handling fumes are not adequately controlled, use respirator approved for protection from organic vapors and acid gases. When dust or powder from secondary operations, such as grinding, sanding or sawing, are not adequately controlled use respirator approved for protection from dust.

9. PHYSICAL AND CHEMICAL PROPERTIES

- PHYSICAL STATE** : Solid
- COLOR AND APPEARANCE** : Plastic pellet with slight odor
- BOILING POINT** : Not Applicable
- MELTING POINT (°C)** : 260 ~ 290
- VAPOR PRESSURE (mmHg)** : Negligible
- VAPOR DENSITY (Air=1)** : Not Applicable
- SPECIFIC GRAVITY** : 1.20 ~ 1.30
- WATER SOLUBILITY** : Insoluble



 LG Chem	PC Compound LUPOY GN5001RFT	Reg. No.	YGN5001RFT
		Version	1.0
		Page	4 / 5

9. PHYSICAL AND CHEMICAL PROPERTIES *(continued)*

SOLVENT SOLUBILITY	: Slightly soluble in strong polar solvent or chlorinated solvents
% VOLATILES	: Negligible
pH	: Not Applicable
ODOR THRESHOLD	: Not Established
EVAPORATION RATE	: Negligible
COEFFICIENT WATER / OIL DISTRIBUTION	: Not Established
COMMENT	: This product does not exhibit a sharp melting point, but softens gradually over a wide temperature range.

10. STABILITY AND REACTIVITY

STABILITY : Stable under recommended conditions of Section 7

REACTIVITY : Not reactive under recommended conditions of handling, storage, processing and use.

CONDITIONS TO AVOID :

Do not exceed melt temperature recommendations in product literature.

In order to avoid autoignition/hazardous decomposition of hot thick masses of plastic, purgings should be collected in small, flat shapes or thin strands to allow for rapid cooling and quenching in water.

Do not allow product to remain in barrel at elevated temperatures for extended periods of time ; purge with a general purpose resin. (See Section 8 for respiratory protection advice)

HAZARDOUS DECOMPOSITION :

Major decomposition gases are oxidized hydrocarbons (probably carbon monoxide) and steam.

Minor components in decomposition gas may be aldehyde, phenolic compounds, etc.

11. TOXICOLOGICAL INFORMATION

Not Available

12. ECOLOGICAL INFORMATION

Not expected to present any significant ecological problems.


13. DISPOSAL CONSIDERATIONS

RCRA HAZARDOUS WASTE :

Products is not a RCRA hazardous waste.

WASTE DISPOSAL :

Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to determine waste classification.

 LG Chem	PC Compound LUPOY GN5001RFT	Reg. No.	YGN5001RFT
		Version	1.0
		Page	5 / 5

14. TRANSPORT INFORMATION

DOT HAZARD CLASS : Not Regulated
PROPER SHIPPING NAME : Not Regulated
IDENTIFICATION NUMBER : Not Listed
TDGA : Not Listed

15. REGULATORY INFORMATION

Listed below are chemical substances subject to supplier notification requirements.

U.S. REGULATIONS :

TSCA INVENTORY STATUS : This product complies with the Chemical Substance Inventory requirements of the US EPA TSCA.

CERCLA SECTION 103 (40CFR302 : Not Listed

SARA SECTION 313 (40CFR372.65: Not Listed

SARA HAZARD CATEGORIES, SARA SECTIONS 311/312 (40CFR370.21)

ACUTE : Not Listed

CHRONIC : Not Listed

FIRE : Not Listed

REACTIVE : Not Listed

SUDDEN RELEASE : Not Listed

STATE REGULATIONS :

California Proposition 65 : Not Listed

EUROPEAN REGULATIONS :

EC NUMBER : Not assigned

16. OTHER INFORMATION

The information submitted in this MSDS is based on our current knowledge and experience.

Because it is not possible to anticipate all conditions of use additional safety precautions may be required, we make no warranty.

ABBREVIATIONS :

ACGIH : American Conference of Governmental Industrial Hygienist

DOT : Department of Transportation

EC : European Communities

EPA : Environmental Protection Agency

IARC : International Agency for Research on Cancer

NOISH : National Institute for Occupational Safety and Health

NTP : National Toxicology Program

OSHA : Occupational Safety and Health Administration

RTECS : Registry of Toxic Effects of Chemical Substances

CAS # : Chemical Abstracts Service Number

RCRA : Resource Conservation and Recovery Act

