

**UL认证 | LOTTE Advanced Materials**

<b>INFINO</b>	Grade	HN-3104
---------------	-------	---------

Component - Plastics E115797  
[guide info]

**LOTTE ADVANCED MATERIALS CO LTD**

56 Gosan-ro, Uiwang-si Gyeonggi-do 437-711 KR

**HN-3104(+)(f1)(M)**

Polycarbonate (PC), glass reinforced "INFINO", furnished as pellets

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
ALL	1.5	V-0	0	1	125	105	120
	3.0	V-0, 5VA	0	0	125	110	125

Comparative Tracking Index (CTI): 3

Dielectric Strength (kV/mm): 23

High-Voltage Arc Tracking Rate (HVTR): 4

Dimensional Stability (%): -

Inclined Plane Tracking (IPT): -

Volume Resistivity (10<sup>x</sup> ohm-cm): 11

High Volt, Low Current Arc Resis (D495): 7

(+) - May be replaced by one, two, or three numbers and/or letter(s)

(M) - IEC CTI Solution B: CTI 125M

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2011-04-08

Last Revised: 2016-12-27

© 2017 UL LLC



**IEC and ISO Test Methods**

Test Name	Test Method	Units	Thk (mm)	Value
Flammability	IEC 60695-11-10, IEC 60695-11-20	Class (color)	1.5	V-0 (ALL)
			3.0	V-0, 5VA (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	°C	1.5	960
			3.0	960
Glow-Wire Ignition (GWIT)	IEC 60695-2-13	°C	1.5	850
			3.0	875
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	3.0	CTI175
IEC Ball Pressure	IEC 60695-10-2	°C	3.0	125
ISO Heat Deflection (1.80 MPa)	ISO 75-2	°C	-	-
ISO Tensile Strength	ISO 527-2	MPa	-	-
ISO Flexural Strength	ISO 178	MPa	-	-
ISO Tensile Impact	ISO 8256	kJ/m <sup>2</sup>	-	-
ISO Izod Impact	ISO 180	kJ/m <sup>2</sup>	-	-
ISO Charpy Impact	ISO 179-2	kJ/m <sup>2</sup>	-	-