SAFETY DATA SHEET

1. Chemical product and company identification

Product name Panlite® DN-5615B

SDS Number DN5615B-JpE

Version number 02

Issue date 04-01-2013 **Revision date** 10-01-2015 Company name TEIJIN Limited.

Address 2-1, Kasumigaseki 3-chome, Chiyoda-ku, Tokyo 100-8585, Japan

Division Environment Quality Assurance Department,

Electric Materials & Performance Polymer Products Business Group

Telephone number +81 3-3506-4717 +81 3-3580-6680

Recommended use of the chemical and restrictions on use

Intended use Molding material for industry use

2. Hazards identification

GHS-classification The product is not classified according to GHS.

GHS label elements None. **Precautionary statement** None.

National/local information See section 15 for regulatory information.

3. Composition/information on ingredients

Substance or Mixture Mixture

Gazette notification

Components	(Alin Miller	CAS#	ENCS no.	ISHL no.	Concentration (%)
Polycarbonate resin	MEHOLICE.	25971-63-5	(7)-738	(7)-738	80 – 90
Talc	Mary Silver	14807-96-6	(1)-468	(1)-468	=< 15

Chemical formula: (C15H16O2.CCl2O)x (25971-63-5), H2-O3-Si 3/4Mg (14807-96-6)

4. First aid measures

If inhaled In case of inhalation of dusts or fumes from heated product: Move injured person into fresh

air and keep person calm under observation. Get medical attention if any discomfort

continues.

If on skin Rinse with water. Get medical attention promptly if symptoms persist or occur after washing.

If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of adhering material and treatment of

If in eyes Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get

medical assistance.

If swallowed Rinse mouth thoroughly. Large quantities: Get medical attention if symptoms occur.

Expected acute and delayed

Symptoms

Talc may have effects on the lungs, resulting in talc pneumoconiosis.

Protection of first-aid responders First aid personnel must be aware of own risk during rescue.

Notes to physician Treat symptomatically.

5. Fire-fighting measures

Extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Extinguishing media to avoid

Specific hazards During fire, gases hazardous to health may be formed.

Special fire fighting procedures

Use standard firefighting procedures and consider the hazards of other involved materials.

Protection of fire-fighters Selection of respiratory protection for fire fighting: follow the general fire precautions

indicated in the workplace.

Panlite® DN-5615B Company name: TEIJIN Limited. SDS JAPAN Version #: 02 Revision date: 2015/10/01 1/4

6. Accidental release measures

Personal precautions. protective equipment and emergency measures

Avoid inhalation of dust. See Section 8 of the SDS for Personal Protective Equipment.

Environmental precautions

Do not allow to enter drains, sewers or watercourses.

Clean-up methods and materials and containment

measures

Collect and dispose of spillage as indicated in Section 13 of the SDS.

7. Handling and storage

Handling

Technical measures Use explosion-proof electrical equipment if airborne dust levels are high.

Local and general ventilation Provide adequate ventilation.

Precautions Use work methods which minimize dust production. Wear appropriate personal protective

Safe handling advice Avoid inhalation of dust. Avoid prolonged or repeated contact with skin. Avoid vapors from

heated materials to prevent exposure to potentially toxic/irritating fumes.

Storage

Technical measures Avoid dust formation.

Suitable storage conditions Store in closed original container in a dry place.

Safe packaging materials Keep in original container.

8. Exposure controls/personal protection

Occupational exposure limits

Japan. OELs - JSOH. (Japan Society of Occupational Health: Advisory Opinion on Permissible [Exposure] Limits)

Components	Туре	Value	Form
Talc (14807-96-6)	TWA	2 mg/m3	Total dust.
		0.5 mg/m3	Respirable dust.
US. ACGIH Threshold Limit Values		- A James Aller	

Components Talc (14807-96-6) **TWA** 2 mg/m3 Respirable fraction.

Engineering measures Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of

inhalation of dust and fumes.

Personal protective equipment

Wear respirator if there is dust formation. When the product is heated, use suitable Respiratory protection

respiratory equipment with gas filter for organic gas.

Hand protection For prolonged or repeated skin contact use suitable protective gloves. When material is

heated, wear gloves to protect against thermal burns.

Use tight fitting goggles if dust is generated. If contact with hot material may occur, safety Eye protection

glasses and face shield are recommended.

Skin and body protection No protection is ordinarily required under normal conditions of use.

Hygiene measures

Always observe good personal hygiene measures, such as washing after handling the

material and before eating, drinking, and/or smoking. Routinely wash work clothing and

protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Pellets. Color Natural. Odor None.

Not applicable. Melting point/Freezing point > 464 °F (> 240 °C) Not applicable. Boiling point, initial boiling

Flash point > 971.6 °F (> 522 °C)

Company name: TEIJIN Limited 2580 Version #: 02

point, and boiling range

Panlite® DN-5615B Revision date: 2015/10/01

SDS JAPAN

Auto-ignition temperature > 1022 °F (> 550 °C)

Combustion characteristics

(solid, gas)

Not available.

Flammability limit - lower (%) Not available.
Flammability limit - upper (%) Not available.
Vapor pressure Not applicable.
Vapor density Not applicable.

Specific gravity 1.31

Solubility Insoluble in water **Partition coefficient** Not available.

(n-octanol/water)

Decomposition temperature Not available.

10. Stability and reactivity

Stability Stable under normal temperature conditions.

Possibility of hazardous reactions Will not occur.

Conditions to avoid None known.

Incompatible materials No data available.

Hazardous decomposition

During combustion: Carbon monoxide. Carbon Dioxide.

products

11. Toxicological information

Acute toxicity May cause discomfort if swallowed.

Skin corrosion/irritation Dust may irritate skin.

Serious eye damage/eye irritation Dust in the eyes will cause irritation. May cause redness and pain.

Respiratory sensitizerNone known.Skin sensitizerNone known.Germ cell mutagenicityNone known.CarcinogenicityNot classified.

ACGIH Carcinogens

Talc (CAS 14807-96-6)

A4 Not classifiable as a human carcinogen.

Toxic to reproduction

Specific target organ toxicity -

single exposure

None known. None known.

Specific target organ toxicity -

repeated exposure

The product contains a substance that may cause damage to organs through prolonged or repeated exposure. Talc may have effects on the lungs, resulting in talc pneumoconiosis.

12. Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, this

does not exclude the possibility that large or frequent spills can have a harmful or damaging

effect on the environment.

Persistence/degradability None known.

Bioaccumulation None known.

Mobility in soil The product is insoluble in water and will sediment in water systems.

Other hazardous effects None known.

13. Disposal considerations

Residual waste Dispose of waste at a facility with special permission to dispose industrial wastes. Waste

should be accompanied by a manifest for the industrial waste. Dispose of in accordance with local regulations. Do not discharge into rivers, lakes, mountains, etc. because the

product may affect the environment.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after

container is emptied.

14. Transport information

International regulations Not regulated as dangerous under UN transport regulation.

IATA Not regulated as dangerous goods.

Company name: TEIJIN Limited. Panlite® DN-5615B
2580 Version #: 02 Panlite® DN-5615B
SDS JAPAN
3/4

IMDG Not regulated as dangerous goods.

15. Regulatory information

Industrial Safety and Health Act

Specified substances regulationNot regulated.Organic solvents regulationNot regulated.Notifiable substancesNot regulated.Labeling substancesNot regulated.

Poisonous and Deleterious Substances Control Act Not regulated.

Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc.

Class I specified chemical substancesNot regulated.Class II specified chemical substancesNot regulated.Monitoring chemical substancesNot regulated.

Law concerning Pollutant Release and Transfer Register

Specified class 1 substances (substance name, ordinance number and content)

Not regulated.

Class 1 substances (substance name, ordinance number and content)

Not regulated.

Class 2 substances (substance name, ordinance number and content)

Not regulated.

Fire Service Act Not dangerous goods under Fire Service Law

Ship Safety Law, Dangerous Goods Marine Transport and Storage Rule

Not regulated.

Air Law, Enforcement Rule

Explosives Control Act

High Pressure Gas Safety Act

Not regulated.

Not regulated.

Act on Prevention of Marine Pollution and Maritime Disaster

Not regulated.

16. Other information

The information about colorant is not contained in this SDS.

This information is provided without warranty. The information is believed to be correct. The precautions in this SDS are intended for normal use. Please take safety measures appropriate to the use and the application when handling the product in a special way. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

All the boundary of the state o

Company name: TEIJIN Limited. 2580 Version #: 02 Panlite® DN-5615B Revision date: 2015/10/01