Need more information? Click Here to go to the iQ™ for Plastics database

Component - Plastics E65424

KUMHO PETROCHEMICAL

KUMHO BLDG 57, 15TH & 16TH FL, 57 SHINMMUNRO, 1-KA, CHONGNO-KU, SEOUL 110-061 KR

HI-425

Polystyrene (PS), furnished as pellets

	Min Thk	Flame			RTI	RTI	RTI
Color	(mm)	Class	HWI	HAI	Elec	Imp	Str
ALL	1.5	НВ	4	1	50	50	50
	3.0	НВ	3	1	50	50	50
CHICK.	6.0	HB	2	1	50	50	50

Comparative Tracking Index (CTI): 1

Dimensional Stability (%): 0.0

High-Voltage Arc Tracking Rate (HVTR):

High Volt, Low Current Arc Resis (D495): 5

Dielectric Strength (kV/mm): 45

Volume Resistivity (10x ohm-cm): 15

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Report Date: 1981-03-23 Last Revised: 2003-10-24

Underwriters Laboratories Inc®



IEC and ISO Test Methods

			inickness	
Test Name	Test Method	Units	Tested (mm)	Value
IEC Flammability	IEC 60695-11-10	Class (color)	1.5	HB75 (ALL)
th ^{all} th.		7 (th)	3.0	HB40 (ALL)
AL PARTY OF THE PA		A AND PROPERTY.	6.0	HB40 (ALL)
Glow-Wire Flammability (GWFI)	IEC 60695-2-12	C	#	- 4
Glow-Wire Ignition (GWIT)	IEC 60695-2-13) c	-	On
IEC Comparative Tracking Index	IEC 60112	Volts (Max)	-	
IEC Ball Pressure	IEC 60695-10-2	С	-	
ISO Heat Deflection (1.80 MPa)	ISO 75-2	С	_	-
ISO Tensile Strength	ISO 527-2	MPa	all En	-
ISO Flexural Strength	ISO 178	MPa	ALIVO, ARIES	-
ISO Tensile Impact	ISO 8256	kJ/m ²	Marital Comment	-
ISO Izod Impact	ISO 180	kJ/m ²	'iga.	
ISO Charpy Impact	ISO 179-2	kJ/m ²	-	W.

Underwriters Laboratories Inc®

The materials covered in this database are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. THE FINAL ACCEPTANCE OF THE COMPONENT IS DEPENDENT UPON ITS INSTALLATION AND USE IN COMPLETE PRODUCTS SUBMITTED TO UNDERWRITERS LABORATORIES INC.

Notice of Disclaimer