

Mitsubishi Chemical Polymer Nantong Co Ltd
NANTONG ECONOMIC & TECH DEV AREA, 6 GUANGZHOU RD, NANTONG JIANGSU 226009 CN



Shinkolite-P, Acrypet: VH6
Polymethyl Methacrylate (PMMA)

| 105 . 16. | . () * * . / () | . C. A. Ver. | |
|-----------------------------|--|---|----------------------|
| Flammability | | Value | Test Method |
| Flame Rating | \$ \$ 5 TO | W. 151" | |
| 1.5 mm, NC, WT | | HB | UL 94 |
| 3.0 mm, NC, WT | | НВ | UL 94 |
| 3.0 mm, NC, WT | | HB40 | IEC 60695-11-10, -20 |
| 1.5 mm, NC, WT | | HB75 | IEC 60695-11-10, -20 |
| Electrical | \bar{\bar{\bar{\bar{\bar{\bar{\bar{ | Value | Test Method |
| Hot-wire Ignition (HWI) | 10 10 | | UL 746 |
| 1.5 mm | | PLC 4 | |
| 3.0 mm | 1 The State of the | PLC 3 | the. |
| High Amp Arc Ignition (HAI) | MFAL CHE | MEN CONTE | UL 746 |
| 1.5 mm | | PLC 0 | |
| 3.0 mm | | PLC 0 | |
| Thermal | | Value | Test Method |
| RTI Elec | | | UL 746 |
| 1.5 mm | 0/12/0 | 50.0 °C | |
| 3.0 mm | 4 Pr 10 11 1 | 50.0 °C | 8 |
| RTI Imp | | . 4 (May 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | UL 746 |
| 1.5 mm | A CEP LE COM | 50.0 °C | ALTO VIE |
| 3.0 mm | | 50.0 °C | All by John |
| RTI Str | | | UL 746 |
| 1.5 mm | | 50.0 °C | |
| 3.0 mm | | 50.0 °C | |
| | | | |

Notice of Disclaimer

By accessing this Yellow Card data information sheet and the database from which this information was generated (the "Yellow Card"), the user acknowledges and accepts the terms and conditions upon which this Yellow Card is made available. This Yellow Card, the database from which it was generated, and all related materials, support, and services, are made available by UL for use only by permission and "as is", without any representation or warranty of any kind, express or implied, including but not limited to any implied warranties of merchantability, fitness for a particular purpose or that the products identified in this Yellow Card will satisfy the user's requirements. UL cannot and does not warrant that the data contained in this Yellow Card is current, accurate, or complete. The user must independently confirm the conformance of any product to the applicable standards or requirements with the manufacturer of that product. Permission to access this Yellow Card may be withdrawn at any time by UL in its sole discretion. The identification of products and companies on this Yellow Card does not in any way imply endorsement of those products or companies by UL. UL does not assume and expressly disclaims, liability to any person for any loss or damage (including lost profits, lost savings, or any indirect, special, incidental, consequential or punitive damages whether or not UL has been advised of the possibility of such damages) arising out of, or in connection with, the use of this Yellow Card regardless of the cause or causes of such loss or damage.

Page 1 of 1 Form Number: E256044-101328774

Report Date: 1/2/2013 Last Revised: 1/2/2013

UL and the UL logo are trademarks of UL LLC Copyright © 2018 All Rights Reserved. | www.ul.com